

Model	Description	Amount
01. City panorama presentation system		
PT-DZ21K2U	Projector, 1920x1080, HD SDI, 200,000 lumens, curvilinear correction, Panasonic	4
ET-D75LE90	Projector Lens, F2.5, 0.36: 1, 7 kg, Panasonic	4
02. TLC kits - 3 pcs.		
AG-CX350	Manual 4K camcorder: 1 inch CMOS, 15MPix, 20x zoom, optical and software stabilizer, 2000TV lines, F13, 10 bit codec, HLG, SDI output, RJ-45, NDI-HX, Panasonic	3
AJ-WM50E	External WiFi adapter, Dual Band Compact Wireless Module, Panasonic	3
MVR901ECLA	Remote Zoom and Focus Control for AG-CX350, RC PAN BAR LANC, Manfrotto	3
AG-VBR118G	11800mAh battery pack for AG-DVX200 / AJ-PX270EJ/ AG-CX350, Panasonic	3
CS-3e	Short gun, no accessories, Sanken	3
1017MS System Ace XL FT	Flowtech 75. Ace XL fluid head (S2150-0004)+ tripod flowtech 75 MS with midlevel spreader and rubber feet (4585) + padded bag flowtech 75 (9116) + carry handle S2051- 1057), Sachtler	1
Ronin-M	Stabilization system for cameras up to 3.6 kg, DJI	2
16x9 Easyrig MiniMax	Camera Support for Cameras Up to 7 kg, Easyrig	2
SDSDXPA-032G-X46	Memory card, SanDisk	6
03. Non-linear editing station, voice acting		
L8T12AV/12	HP Z240 Tower [Core i7-6700 (3,4GHz, 8MB Cache, 4 Cores), 16GB (4x4GB) DDR4 RAM, 128GB SSD, HDD 1TB, DVDRW, Kbd, Mouse, Win 10/7 Pro 64B, 3Y, HP	1
DeckLink Studio 4K	Interface Board, 10 bit SD/HD-SDI/YUV/VBS/YC i/o, Genlock, AES/AA i/o, RS-422, Blackmagicdesign	1
EPR8-ST-DL	EDIUS Pro 8 (serial key), GrassValley	1
G1S79AA	Card reader HP 15-in-1 USB2/3 3.5 Media Card Reader - 15-in-1 - Memory Stick, Secure Digital (SD) Card, MultiMediaCard (MMC) - USB 3.0, HP	1
P2717H	27 "matte WLED IPS monitor (1920x1080), USB, HDMI, DP, VGA, DELL	2
Yamaha AG06	6-channel mixer / USB interface. Inputs: 2x XLR, 2x TRS, 2x RCA. Outputs: 2x TRS (ST OUT), 2x TRS (MON OUT), 1x Headphones. Headset in / out, USB, Yamaha	1
MSP-3	Audio Monitor, Active, 20W, Yamaha	2
DT 770 PRO	Studio Headphones, 250 Ohm, Beyerdynamic	1

K 190.00	Headset cable (DT290) without connectors, Beyerdynamic	1
DT 291 PV MK II LTD	DT 291 PV MK II LTD, with limiter, 250 ohms, for phantom power, Beyerdynamic	1

04. Production System Newtek TC1

TC1DBDL	Production system TriCaster TC1 DELUXE Bundle (TriCaster TC1 2RU, NC1 I / O and TC1LP), NewTek	1
P2717H	27 "matte WLED IPS monitor (1920x1080), USB, HDMI, DP, VGA, DELL	3
RP5 G3	Acoustic system KRK ROKIT RP5 G3, 50 W, speakers 5 "LF + 1" HF, 45 Hz-35 kHz, KRK	2
LVM-212W	21.5 "3Gb / HD / SD LCD monitor, 1920x1080, 1xHDMI input, 1xDVI, 2x3G SDI input, 3xAnalog, audio de-embedder, internal speaker, oscilloscope / vectroscope, TVlogic	3
LVM-241S	Monocrystal 24 inch, 1920x1080 ,. 10-bit panel, 3D LUT, oscilloscope / vectoroscope, Fast Mode, TVlogic	1

05. Titles and issue on the video wall Character Works

CW Broadcast	CharacterWorks Broadcast is a graphic design system with support for the iVGA and NDI interfaces for connecting to Tricaster. 3D, animated graphics, timeline, keyframes, creeping lines, data from external sources, CharacterWorks	2
CW Capture Input	CharacterWorks Decklink Capture Input - option to activate the Decklink video input, CharacterWorks	2
CW TriCaster Remote	CharacterWorks TriCaster Remote - option for managing media players and macros TriCaster, CharacterWorks	2
DeckLink Duo 2	4-channel PCIe-card for storage and video recording SD- and HD-video up to 1080p / 60, Blackmagicdesign	2
DeckLink SDI 4K	Interface Board, SDI, HD-SDI i / o, Genlock, Blackmagicdesign	4
CW Dual Channel	CharacterWorks Dual Channel - option to activate the second video output iVGA / NDI or SDI (two independent titles in one computer), CharacterWorks	2
P2717H	27 "matte WLED IPS monitor (1920x1080), USB, HDMI, DP, VGA, DELL	2
F5W13AV/DC11	Xeon E5-1620 v3 (3,5GHz, 10MB Cache, 4 Cores), 16GB (2x8GB) DDR4-2133 RAM, 512GB SSD + 1TB SATA HDD, DVDRW, No Graphics, Kbd, Opt.Mouse, Win 8.1/7 Pro 64B, 3YW, HP	2
GTX 1080	Video card Asus PCI-Ex GeForce GTX 1080 8GB DDR5X, Asus	2
SDI to HDMI 4K	Converting SDI to SD / HD and Ultra HD to HDMI 4K with analog audio and AES audio, Blackmagicdesign	8

06. Audio equipment

Si Performer 1	Digital audio mixer, 16 mikr, 8 lin, 4 stereo, 16 motor fader, 8 VCA, 8 mute group, 80 input to miksu, 20 vikh.shin, 4 percent. Lexicon, Equalization. parameters., graphs, compressors, video faders, 2 slots for retail, DMX, red ribbon, Soundcraft	1
MKH60-1	Directional microphone, super-cardioid, 50-20000 Hz, 48V, Sennheiser	2
MZS-40-0	Microphone mount with vibration isolation, Sennheiser	2
23770	Microphone holder type "fishing rod", length: 1200 - 4600 mm, maximum load: 0.5 kg, Konig & Meyer	2
RP5 G3	Acoustic system KRK ROKIT RP5 G3, 50 W, speakers 5 "LF + 1" HF, 45 Hz-35 kHz, KRK	2
EW 300 IEM G3	Monitoring System, Sennheiser	2
CES-2	Hidden monitoring earphone for monitoring: RTV-04, CMT-98, ET-4, cord, & 1/8 plug, beige, Telex	2
BT-2	Set of standard ear plugs for ET-2, 5pcs, Small, Telex	1
BT-3	Set of standard ear plugs for ET-2, 5pcs, Medium, Telex	1
BT-4	Set of standard earplugs for ET-2, 5pcs, Large, Telex	1
SK 2000	Miniature UHF Transmitter, Sennheiser	8
COS-11DR-BE/1,6 Lemo 3pin	Lavalier microphone, 1.6m, accessory kit, Lemo3 for SK50,250,3000,5000, corporal, Sanken	4
COS-11DR-BK/1,6 Lemo 3pin	Lavalier microphone, 1.6m, accessory kit, Lemo3 for SK50,250,3000,5000, black, Sanken	4
SKP 2000 DW	Transmitter plug-on 2000 series ranges A / B / C / D / G, Sennheiser	2
EK 2000	2000 Series Portable Receiver, Sennheiser	2
HD300 PRO	64 Ohm Closed Studio Headphones, Sennheiser	2
EM 2050	Dual Channel UHF Receiver, NET Control, Sennheiser	4
A 1031-U	450-960 MHz passive omnidirectional receive / transmit antenna, Sennheiser	4
AB 3	Antenna Amplifier, Sennheiser	4
ASA 1	Active Antenna Splitter 2x1: 4, Sennheiser	4
NT 1-1-EU	Power supply for antenna splitter ASA 1, Sennheiser	4

07. Office communication

CR4	19 ", 4-channel control panel Digital Party Line, Riedel	2
CR2	19 ", 2-channel control panel Digital Party Line, Riedel	1
MIC-30	Microphone "goose shiya" for subscriber panels of all series, electric 30cm., Riedel	3
TX300V	Transmitter Phonak TX-300V Set studio transmitter 20 channels 150-220MHz, Phonak	2
INVISITY 4CH Flex	4-channel receiver with programmable frequencies, Phonak	8

08. Ethernet network 48x1G

GS752TX-100NES	48 Ethernet ports 10/100/1000 Mb / s Stack Port - 2 x Expansion Slots - 10GBase-T, 10GBase-X, 10/100 / 1000Base-T - 2 x SFP + Slots, Netgear	1
----------------	--	---

08. Video Wall Monitoring Computer

L8T12AV/DC22	HP Z240 Tower [Core i7-6700 (3,4GHz, 8MB Cache, 4 Cores), 16GB (2x8GB) DDR4-2133 nECC RAM, 512GB SSD, HDD 3TB DVDRW, CardReader, , Kbd, Mouse, Win 10/7 Pro 64B, 3Y], HP	1
P2717H	27 "matte WLED IPS monitor (1920x1080), USB, HDMI, DP, VGA, DELL	3

10. Racks, cables, extension cords

	Mobile rack cabinet for equipment, 24 units	2

11. A set of technological furniture

KTM-CR1	Hardware technological furniture set	1

12. Set of light

TVL PANEL DW	LED panel, Bi-Color, 55x40cm, 2x200W, DMX / RDM, 8-petal. Blind, Elation	19
Grid 40° TVL-PANEL	40 ° grille for TVL-PANEL DW, Elation panel	19
620-10	28mm male adapter, M10, Manfrotto	55
C337	Quick Action clamp 1 1/8 "sckt" clamp, Manfrotto	19
LG-G260	LED Panel, Ultra-Matte, 800x400, 280W, 2700-7000K, RGB, Magic Hue, DMX, Blind, Case, Ledgo	3
Louver LG-G260	Black Play for LG-G260, Ledgo	3
B303	Combo stand, max height - 347cm, min - 145cm, max load - 40kg, o48,42,36mm/o25x25mm, Lgrip	3
SYS-FT44U	FreeStyle T44 LED DMX System, Univ (Includes FreeStyle T44 Fixture, Louver 90°, FreeStyle 140 LED DMX Controller, MTP-KG41 Mount, 25ft Head Extension, FreeStyle 4ft LED Tube (x4), KinoFlo	2
A202	Combo stand, max height - 347cm, min - 145cm, max load - 20kg, o42,36,30mm/o25mm, Lgrip	2
L0.33670.X	Arri D25 set: daylight fresnel 2500W, EB2500, barndoor, filterframe, ARRI	1
D804	Wind-up stand, max height - 610cm, min - 190cm, max load - 70kg (B150), Lgrip	1
KL FRESNEL 8 CW PO	LED Fresnel, 350W, 5600K, DMX / RDM, 8-Blind Blind. in kit, PO, Elation	36

	Switching accessories	1
7225A1001-EU	ColorSource 40 control panel, 80 channels (devices) of control, ETC	1
13. Optional		
Pillar 100x100x6000	,	13
Staircase 8500	,	16
Pipe 50x2x6000	,	12
OMP-45	Omega Tube mounting plate D40 ... 50, SRS	148
MP100x100-5	Plate for mounting rails T60, T64, T50, T80, SRS	52